



Liquidtight Product Equivalency Chart

Compare LIQUID-TUFF™ to other brands



AFC LIQUID-TUFF™	ELECTRI-FLEX Liquatite®	ANAMET SEALTITE®	ALFLEX ULTRATITE®
Metal			
Type VF Non-UL 60C/60C/60C/-20C	Type LT – Non-UL PVC 80C/-20C TYPE EF – Non-UL PVC 80C/60C/60C/-20C	Type EFST – Non-UL PVC 60C/60C/60C/-20C TYPE EF – Non-UL PVC 60C/60C/60C/-20C	Type EF – Non-UL PVC 60C/-10C
Type OR/Hi Temp – Non-UL PVC 105C/60C/70C/-26C	Type LOR – Non-UL PVC 60C/60C/60C/-20C	Type OR – Non-UL PVC 105C/60C/60C/-23C	
Type LFMC UL & CSA PVC 80C/60C/70C/-30C	Type LA – UL & CSA PVC 60C/60C/60C/-20C	Type UA – UL & CSA PVC 60C/60C/60C/-20C	Type UL – UL & CSA PVC 80C/60C/60C/-30C TYPE OR UL Listed PVC 80C/60C/60C/-30C
Type COMPUTER BLUE – LFMC UL & CSA PVC 80C/60C/70C/-30C	Type CBLA – UL & CSA PVC 60C/60C/60C/-20C	Type CW – UL & CSA PVC 60C/60C/60C/-20C	Type CB – UL & CSA PVC 80C/60C/60C/-30C TYPE OR UL Listed PVC 80C/60C/60C/-30C
Type HI/LOW TEMP – LFMC UL PVC 105C/60C/70C/-55C	Type ATLA UL & CSA PVC 105C/60C/70C/-55 Type AT Non-UL PVC 105C/-55C	Type HTUA UL PVC 105C/-46C Type HC High/Low Non-UL PVC 105C/-46C	Type HC UL Pending PVC 105C/-40C
EXTREME TEMP – Non-UL TPR 150C/60C/60C/-60C	Type ATX Extreme Temperature Non-UL TPR 150C/-60C	Type HCX Extreme Temperature Non-UL TPR 150C/-60C	
Type LSZH - Flame Retard. Non-UL TPU 80C/60C/70C/-40C	Type CEA – LSZH - Flame Retard. Non-UL TPU 80C/-40C		TYPE NH – LSZH - Flame Retard. Non-UL 60C/-10C
Type LSZH - Flame Retard. TPU LFMC UL 360 80C/60C/70C/-40C	Type ZHLA – LSZH - Flame Retard. TPU UL 360 80C/60C/70C/-40C	Type ZHC – LSZH - Flame Retard. TPO UL 360 82C/-46C	
Non-Metallic			
Type LFNC-A ORANGE Layered NM – LFNC-A UL PVC/NYLON/PVC 80C/60C/60C/-20C	Type LNM-P (orange) Layered NM – LFNC-A UL & CSA PVC/NYLON/PVC 60C/-20C	Type CNP (orange or gray) Layer NM – LFNC-A UL & CSA PVC/NYLON/PVC 60C/-20C	
Type LFNC-B (gray) Integral NM – LFNC-B UL & CSA Rigid PVC/PVC 80C/60C/70C/-20C	Type NM (gray) Integral NM – LFNC-B UL & CSA Rigid PVC/PVC 80C/60C/70C/-20C	Type NMUA (gray) Integral NM – LFNC-B UL & CSA Rigid PVC/PVC 75C/60C/70C/-27C	Type NM Integral NM – LFNC-B UL & CSA Rigid PVC/PVC 80C/60C/60C/-30C Type NMOR Integral NM – LFNC-B UL & CSA Rigid PVC/PVC 80C/60C/60C/-30C
Type LFNC-B HIGH TEMP NM (black) - Integral NM UL Rigid PVC/PVC – LFNC-B 105C/60C/70C/-20C	Type NMHT (black) Integral NM – LFNC-B UL Rigid PVC/PVC 105C/60C/70C/-20C		Type NMHC Integral NM – LFNC-B UL Rigid PVC/PVC 105C/60C/60C/-40C
ULTRAFLEX (black)  Recognized Component NON-UL NM LIQUID-TIGHT 60C/60C/60C/-20C	Type NM2 (black) Integral NM Tubing UL Recognized Component CSA Certified Tubing 70C/-20C		Type NMEF Integral NM Tubing UL Recognized Component CSA Certified Tubing No Temperature